



## ULTIMA PRO AMPLIFIERS 171.207

These Pro amplifiers set the standard in build quality, reliability and features, making this range a formidable force in the market place for price and performance.

- Outstanding sound quality
- Innovative heatsink structure and temperature controlled fan ensure long, reliable operation
- Stereo and bridge modes
- Clip limiter to reduce distortion
- LF filter switch 5Hz, 25Hz, 50Hz
- Signal, overload and bridge LED indicators for each channel
- Balanced (XLR) and unbalanced (6.3mm) inputs
- Speakon® (NL4) and binding post outputs
- Robust construction and 19" rack mountable

<b>Power supply</b>	230Vac, 50Hz
<b>Crosstalk</b>	>75dB
<b>Frequency response</b>	20Hz - 20kHz
<b>Input impedance : Balanced</b>	10k ohms
<b>Input impedance : Unbalanced</b>	20k ohms
<b>S/N ratio</b>	>108dB (A-weight)
<b>THD</b>	<0.05%

### Caratteristiche principali:

Power rms : 4 Ohms 2 x 800W  
Power rms : 8 Ohms 2 x 500W  
Bridged mode @ 8 Ohms 1600W  
Damping factor >350  
Slew rate >70/μs  
Dimensions 483 x 375 x 88mm (2U)  
Weight 17kg